CLASSIC CHIP

CC3M18080E

800V G2 Silicon Carbide Power MOSFET

N-Channel Enhancement Mode

V_{DS} = 800V

$R_{DS(ON)}$ = 180mΩ

$I_{D(MAX)@25^{\circ}C}$ = 16.2A

Features

- High blocking voltage with low on-resistance
- High speed switching with low capacitances
- Very low switching losses
- Avalanche ruggedness
- Temperature independent turn-off switching losses
- Integrated lumped gate resistance
- Robust against parasitic turn-on even at 0V turn-off gate voltage





Benefits

- Higher system efficiency
- Reduce cooling requirements
- Increase power density
- Increase system switching frequency

Applications

- PD Charger
- High voltage DC/DC converters
- Switch mode power supplies
- EV battery chargers
- PV inverters

Part number	Package Type
CC3M18080E	TO-252-3L

Maximum Ratings (T_C=25˚C unless otherwise specified)

Symbol	Parameter	Value	Unit	Test Conditions
V_{DSmax}	Drain - Source Voltage	800	V	V_{GS} = 0V, I_D = 100μA
V_{GSmax}	Gate - Source Voltage	-10 /+22	V	Absolute maximum values
V_{GSop}	Gate - Source Voltage	-5 /+18	V	Recommended operational values
I_D	Continuous Drain Current	16.2	A	V_{GS} = 18V, T_C = 25˚C
		11.5		V_{GS} = 18V, T_C = 100˚C
$I_{D(pluse)}$	Pulsed Drain Current	26	A	Pulse width t_P limited by $T_{j,max}$
P_D	Power Dissipation	68	W	T_C = 25˚C, T_J = 175˚C
T_J, T_{stg}	Operating Junction and Storage Temperature	-55 to +175	˚C	/
T_L	Soldering Temperature	260	˚C	1.6mm (0.063”) from case for 10s

Electrical Characteristics (T_C = 25˚C unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	800	-	-	V	V_{GS} = 0V, I_D = 100μA
$V_{GS(th)}$	Gate Threshold Voltage	2.0	3.0	4.0	V	V_{DS} = V_{GS}, I_D = 3mA
		-	2.1	-		V_{DS} = V_{GS}, I_D = 3mA T_J = 175˚C
I_{DSS}	Zero Gate Voltage Drain Current	-	1	10	μA	V_{DS} = 800V, V_{GS} = 0V
I_{GSS}	Gate-Source Leakage Current	-	-	200	nA	V_{GS} = 22V, V_{DS} = 0V
		-200	-	-	nA	V_{GS} = -10V, V_{DS} = 0V
$R_{DS(on)}$	Drain-Source On-State Resistance	-	180	250	mΩ	V_{GS} = 18V, I_D = 8A
		-	240	-		V_{GS} = 18V, I_D = 8A T_J = 175˚C
g_{fs}	Transconductance	-	10	-	S	V_{DS} = 20V, I_D = 8A
		-	-	-		V_{DS} = 20V, I_D = 8A T_J = 175˚C
C_{iss}	Input Capacitance	-	281	-	pF	V_{DS} = 400V V_{GS} = 0V f = 1MHz, V_{AC}=25mV
C_{oss}	Output Capacitance	-	35	-		
C_{rss}	Reverse Transfer Capacitance	-	3	-		
E_{oss}	C_{oss} Stored Energy	-	5.0	-	μJ	
E_{ON}	Turn-On Switching Energy	-	26	-	μJ	V_{DS} = 400V V_{GS} = -5/+18V, I_D = 8A R_G = 2.5Ω
E_{OFF}	Turn-Off Switching Energy	-	5	-		
$t_{d(on)}$	Turn-On Delay Time	-	6	-	ns	
t_r	Rise Time	-	8	-		
$t_{d(off)}$	Turn-Off Delay Time	-	8	-		
t_f	Fall Time	-	10	-		
$R_{g(int)}$	Internal Gate Resistance	-	12	-	Ω	V_{AC}=25mV, f = 1MHz
Q_{gs}	Gate to Source Charge	-	2	-	nC	V_{DS} = 400V V_{GS} = -5/+18V, I_D = 8A
Q_{gd}	Gate to Drain Charge	-	6	-		
Q_g	Total Gate Charge	-	13	-		

Reverse Diode Characteristics (T_C = 25˚C unless otherwise specified)

Symbol	Parameter	Typ.	Max.	Unit	Test Conditions
V_{SD}	Diode Forward Voltage	4.0	-	V	V_{GS} = -5V, I_{SD} = 4A
		3.7	-		V_{GS} = -5V, I_{SD} = 4A T_J = 175˚C
I_{SD}	Continuous Diode Forward Current	-	15	A	V_{GS} = -5V
		-	8		V_{GS} = -5V, T_C = 100˚C
t_{rr}	Reverse Recover Time	9	-	ns	V_{DD} = 400V, V_{GS} = -5V I_{SD} = 8A di/dt = 1000A/μs
Q_{rr}	Reverse Recovery Charge	30	-	nC	
I_{rrm}	Peak Reverse Recovery Current	5	-	A	

Thermal/Package Characteristics

Symbol	Parameter	Typ.	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case	2.2	˚C/W

Package Dimensions

TO-252-3L Package Outline



Dim	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	2.20	2.50	0.087	0.094
A1	1.00	1.40	0.039	0.055
A2	0.00	0.15	0.000	0.006
b	0.50	0.70	0.020	0.028
b1	0.70	0.90	0.028	0.035
c	0.40	0.60	0.016	0.024
c1	0.40	0.60	0.016	0.024
D	6.20	6.70	0.244	0.264
D1	5.10	5.50	0.201	0.217
D2	2.70	3.20	0.106	0.126
E	5.20	5.80	0.205	0.228
E1	1.20	1.60	0.047	0.063
E2	5.00	5.60	0.197	0.220
e	2.20	2.40	0.087	0.094
e1	4.40	4.80	0.173	0.189
L	9.70	10.40	0.382	0.409
L1	1.40	1.70	0.055	0.063
L2	0.60	1.20	0.024	0.047

Revision History

Document Version	Date of Release	Brief Summary
Rev.0.1	2026-04-25	Draft.

Notes & Disclaimer

- This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by CLASSIC C HIP. No communication from any employee or agent of CLASSIC CHIP or any third party shall effect an amendment or modification of this document. No responsibility is assumed by CLASSIC CHIP f or any infringement of patents or other rights of third parties which may result from use of the inform ation contained herein. No license is granted by implication or otherwise under any patent or patent ri
- ghts of CLASSIC CHIP.
  We assume no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all products described or contained
- herein.
  Notwithstanding any application-specific information, guidance, assistance, or support that CLASSI C CHIP may provide, the buyer of this product is solely responsible for determining the suitabilit y of this product for the buyer's purposes, including without limitation for use in the applications ide ntified in the next bullet point, and for the compliance of the buyers' products, including those that in
- corporate this product, with all applicable legal, regulatory, and safety-related requirements.
  This product has not been designed or tested for use in, and is not intended for use in, applications in which failure of the product would reasonably be expected to cause death, personal injury, or property damage, including but not limited to equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment, aircraft navigation, communication, and control systems, aircraft power and propulsion systems, air traffic control systems, and equipment used in the planning, construction, maintenance, or operation of nuclear
- facilities.
  RoHS Compliance
  The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted
- application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013.
  REACh Compliance
  REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your CLASSIC CHIP representative to ensure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information is also a vailable upon request.